

Specifications
 Voltage Rating: 250V(AC,DC)
 Current Rating: 4A(AC,DC)
 Insulation Resistance: 1000MΩ Min.
 Dielectric Withstanding: 1000VAC/minute
 Contact Resistance: 20mΩ Max.
 Operating Temperature: -25°C to +85°C

Wafer
 Contact Material: Brass
 Base Material: Nylon 66, UL 94V-0
 All materials must meet Greenconn requirement for environment protection.


No. of Pins/Row	Dimension	
	L	M
02	4.98	2.54
03	7.52	5.08
04	10.06	7.62
05	12.60	10.16
06	15.14	12.70
07	17.68	15.24
08	20.22	17.78
09	22.76	20.32
10	25.30	22.86
11	27.84	25.40
12	30.38	27.94
13	32.92	30.48
14	35.46	33.02
15	38.00	35.56
16	40.54	38.10
17	43.08	40.64
18	45.62	43.18
19	48.16	45.72
20	50.70	48.26

Ordering Information

G WHB103- XX XX A 010 E 5 B X

NO. of Pins per row: 02~20
 Standard Plating: 01=Tin, Selective plating, 02=Gold Flash
 Color: 5=beige
 Standard: N=PE Bag

Recommended P.C.Board
 Thickness=1.20,(Tolerance:+/-0.05)



格菱股份有限公司
Greenconn Corporation

REV. A	UNIT. mm	SCALE. 1:1	PAGE. 1/1	GENERAL TOLERANCE		DESIGN:	DATE:	DWG. NO. GWHB103-CA10EB	TITLE. PITCH 2.54 WAFER 90°
				.X* ± /	X. ± /	CHECKED:	DATE:		
				.XX* ± 1.0*	.XX ± 0.25	APPROVED:	DATE:		
				.XX* ± 1.0*	.XX ± 0.20			PART NO. GWHB103-XXXXA010E5BX	
				.XXX* ± 0.3*	.XXX ± 0.1				